

125K-R-TTL-M1

125K EM4100 Slim size RFID Reader Module with TTL interface

General Description

This is a low cost high performance, super mini size RFID reader module for EM4100 Manchester encoded and RF/64 read only transponders. All complex antenna driver, RF receiver and decoding are handled by the module.

Features

- High sensitivity, reliable performance
- Embedded antenna design
- Ultra Compact, small outline
- Support UART-TTL interface
- easy for operation
- Waterproof design





Specifications

- **Power** : 5 Volts +/-0.15Volt DC, 80mA typical
- **Interface** : UART (TTL level)
- **Reading Range** : 2-4cm for ISO Card size
- **Frquency** : 125KHz
- **Support Tag** : 125Khz EM4100 or compatible tag
- **Operating temperature** : -0°C to + 85°C
- **diameter** : 24 mm / **Thickness** : 8 mm

Pin Assignment

Pin 1	Pin 2	Pin 3	Pin 4
-------	-------	-------	-------



Pin 7	Pin 6	Pin 5
-------	-------	-------

Pin out	RS232(TTL level)
1	NC
2	Vdd 5V DC
3	GND
4	NC
5	TTL serial Data out
6	NC
7	NC

Data Format

Baud Rate: 9600, N, 8, 1

STX (Start String)	Card data	Checksum	ETX (End String)
(1 byte) 0x55	(4 Byte Hex)	(1 Byte Hex)	(1 byte) 0xAA

Checksum : XOR Card Data (Total 4 Byte)