

All 3 Track / Dual Track

Magnetic card Reader /writer with RS232 interface

APPLICATIONS:

This magnetic card reader/writer is used in information in magnetic bar of reader/writer credit card, magcard and bankbook. It is widely used in the industries such as finance, post, commerce, traffic & custom.

PRODUCT FEATURES

- high speed or low speed for pulling card support
- Super long life of magnetic head under heavy load work
- Support Lo-Co magnetic card read/write
- ISO record format support
- Sound and light indication
- Low power & Low cost
- High performance & High reliability

SPECIFICATION :

- Card pulling speed : 10-120cm/s
- Support standard : ISO7810-7811-1,2,3,5/IBM
- record density : track 1 (210 BPI)
: track 2 (75 BPI)
: track 3 (210 BPI)
- record character : track 1 (79 Alphanumeric characters)
: track 2 (37 Numeric characters)
: track 3 (104 Numeric characters)

DIMENSION

- 230(L)x60(W)x60(H) mm

POWER SUPPLY

- Voltage : 5V/DC +/- 10% (Power from PS2 Keyboard port)
- Current : 200mA

LIFE CYCLE

- > 600,000 times

INTERFACE:

- RS232 communication with PC

ENVIRONMENT:

- Operation temperature : 0°C To +40°C
- Humidity : 10%-85%RH

Ordering Part No :

Part No	No. of Track support	Interface
MC-T12-RW-232	Dual Track 1&2 magnetic card reader/writer	RS232
MC-T23-RW-232	Dual Track 2&3 magnetic card reader/writer	RS232
MC-T123-RW-232	All 3 Trace magnetic card reader/writer	RS232

